



Precautions to ensure safe usage







The precautions given below are intended to ensure safe and correct use of the products.
Note that certain restrictions apply to use of these products. Failure to observe these could result in injury or property damage.

 Warning	A potentially hazardous situation which could result in death or serious injury.
 Caution	A dangerous situation which could result in minor or medium injury and/or in which only property damage is foreseen.

Note: See the terminology glosses on our website for words marked with a ※.

TOYOCONNECTOR TC6-CS Stainless Steel (TOYOX Hose Dedicated Coupling)



① Notes for installation

-  **Caution** This coupling is not designed for regular disassembly cleaning.
-  **Warning** Hose replacement and coupling disassembly must be performed after the coupling is cooled to room temperature.
There is a risk of burns or damage to the couplings.
 1. When cutting a hose, make sure that the edge face of the hose is cut perpendicularly.
 2. When any lint or hard wire is left at the end of the hose, remove it with pliers or similar tool.
Make sure that no hose fragments, lint, or hard wire is stuck in the hose.
 3. Secure an adequate hose length to avoid bending stress on the hose near the coupling.
 4. Make sure that the hose is inserted completely into the root of the nozzle.
 5.  **Warning** When inserting hoses, never apply oil, etc., to the surface of the nipples. It may cause the hose to become disconnected.
 6. After the orientation of each part is checked, tighten the clamp.
 7. Be careful to avoid injury due to tool slips when fastening.
 8. To fasten, use a hex wrench of length 180 mm or more (200 mm or more for TC6-CS 50).
Tighten the two bolts evenly, and fasten until there are no gaps.
When used in a state where there are gaps, trouble due to fluid leakage or hose disconnection will occur.
When tightening bolts, do not use an impact screwdriver. This may cause damage to the clamp screws.
 9.  **Caution** Unbalanced tightening cannot be fully completed.
 9.  **Caution** NSF "H1" lubricant (extreme-pressure grease), registered as "permitted for use in locations where there is a possibility of incidental contact with food," is applied to the clamp screw parts.
 10.  **Caution** Very occasionally, resin or metal chip dust (or threads) may transpire when fastening. Remove completely before use.
 11. Be careful that incompatible chemicals do not adhere to the rubber components used in the couplings.

② Notes for connecting couplings


1. Select the main unit and gasket materials suitable for the fluid used.
2. Chemicals which are dangerous when permeating (active gases, etc.) should not be used in gaseous form.
3. Use the products within their intended working pressure range.
4. Do not apply external force (e.g. impact) to the body and cam arm. This may cause damage.
5. Avoid pulling or dragging the hoses on the floor. Doing so may cause the cam arms to catch against an object and unlock.
6. Avoid applying loads on joints. This may cause fluid spills.
7. We recommend using couplers and adapters made of the same material when connecting fittings.
Using couplers and adapters made of different materials may lead to corrosion (electrical corrosion).
8. Dismantle the coupler connection only after confirming that there is no residual pressure or materials.
9. To avoid burns during use with high-temperature fluids, avoid direct contact with the coupling.
10. Wear gloves and safety shoes to prevent injury during installation and operation.
11. When vertically installing the coupler, position it on the lower side of the adaptor.
12. High fluid flow rates may result in cavitation that abrades or damages the inner surface of the coupler. Perform inspections at the appropriate intervals.
13. When connecting the coupler, chip dust may transpire due to cam arm tightening. Remove chip dust before use.

③ Notes for safe usage

1. TOYOCONNECTOR is a coupling dedicated for the above TOYOX Hoses. TOYOX is not liable for any damages caused by use with any other hose including those produced by TOYOX as well as those by other manufacturers, as full performance may not be achieved or maintained.
2. Use within the operating temperature and pressure ranges of the applicable hose.
3. In the case of use under negative pressure, negative-pressure usable hoses may not be applicable depending on applications or conditions (temperature, movements, etc.).
4. Do not use a hose that is extremely bent near a coupling. The bending radius of a hose should be larger than its ※3 minimum bending radius.
5.  **Warning** Do not attempt assembly or disassembly of couplings while fluid is running through the hose.
This may cause fluid leakage or hose disconnection.
6. Do not use in locations subject to vibration or impact. This may cause coupling damage or hose disconnection.
7. Perform periodic inspections during and before use to make sure that hose disconnection from the coupling, fluid leakage, and bolt loosening do not take place.
8. Do not allow anything other than the inner surface of the couplings or hose to come in contact with fluids, because the fluids may permeate the hose reinforcement layer or remain inside the couplings, and bacteria may propagate (attach to the parts) or the hose may deteriorate. Also, dust, hose fragments (reinforcement material) and ink adhering to the outer surface may be mixed in.
9.  **Warning** Do not use for piping in the applications below. This may cause coupling damage, hose rupture, or hose disconnection.
 - For piping such as solenoid valve piping, which would apply impact to the piping
 - Where vibration or impact will be applied to the coupling
 - Where the maximum operating temperature is exceeded
 - Where constant tensile stress may be applied to the hoses
 - In a way that may cause static buildup (electric shock hazard)
10. Before use, be sure to disinfect and sterilize the interior of the hose. (Sterilization is not carried out at shipping.)
11. Do not rub the surface with a hard brush, etc., when washing it. The surface could be damaged, causing germs to accumulate.
12. Store in a cool, dry place not subject to direct sunlight. Store keeping the inside of the coupling free from foreign matter and dust.
13. The hose should be disposed of in accordance with the requirements of the local region.
14. Use dust plugs and dust caps to prevent accumulating dust and damage or deformation of the sealing surface.
15. Remove residual fluid from the main unit after use.

④ Notes for gaskets

1. Before using the coupler, check to confirm that the gasket fits into the coupler groove. (See figure to the right)
2. Foreign matter adhering to the gasket seat can make it hard to close the cam arms and may lead to leakage. Inspect and remove any foreign matter.
3. Because gaskets using Teflon (PTFE) solids or Teflon lack elasticity, they may leak depending on conditions of use.
4. Assess the force required to close the cam arms when connecting or disconnecting the couplers. If the force required is too low, the gasket seal may be compromised. In this case, we recommend replacing the gasket.
※ If closing the cam arms feels too easy even after replacing the gasket, the main unit may be damaged. If so, replace the main unit.



⑤ Notes for inspections

1. Startup inspections: Before starting operations, check to confirm that the fittings are free of abnormalities and that the cam arms are fully closed.
2. Regular inspection: During periods in use, be sure to perform regular inspections.

What to do if an abnormality is found

If you observe signs of abnormalities like those below during startup inspections or periodic inspections, stop using the product immediately. Replace with a new product.

1. The main unit or any of the components show large scratches, cracks, deformation, or projecting pins. (The service life of the main unit, cam arms, and gaskets depends on materials and usage conditions. We recommend replacement at periodic intervals.)
2. Closing the cam arms feels too easy when connecting or disconnecting couplers.


⑥ Notes for the reuse of couplings and replacement of hoses

1. When reusing a TOYOCONNECTOR product, make sure that each of its components is not damaged prior to use. Be sure to replace the rubber cap. Be sure to apply commercially available lubricant (extreme-pressure grease) to the bolt screw parts and the clamp before fastening. We recommend the use of NSF "H1" lubricant (extreme-pressure grease), registered as "permitted for use in locations where there is a possibility of incidental contact with food."
2. Before replacing a hose, always make sure to remove the fluid and dirt on the coupling surface. This may cause fluid leakage or hose disconnection.
3. When reusing TOYOCONNECTOR, be sure to use a new hose.
4. While it may vary according to conditions of use, consider five disassemblies a rough guideline for replacing parts or using a new clamp set.
5. Do not hit the coupling with a hammer or similar tool.

⑦ Warning

1. The fluid path (interior) of TOYOCONNECTOR uses SCS 14 (SUS 316 equivalent) material. Phenomena such as corrosion or fluid leaks may occur depending on the type of fluid. Before use, be sure to check data (refer to data on chemical resistance in the catalog or on the website) or make inquiries to the toll-free number. As well, make similar checks for fluid contact with the outer surface of couplings.
2. Do not install or use twisted hoses. Twisted hoses are dangerous because they deform their interior structures and cause hose ruptures. Fix twisted hoses appropriately as shown in the following examples.

Example 1: Hose twisted when it is installed



Example 2: Hose twisted when it is bent

